



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/798,762	03/11/2004	Frank A. Costantini	LCOM-0657	6411
23377 7590 12/14/2007 WOODCOCK WASHBURN LLP CIRA CENTRE, 12TH FLOOR 2929 ARCH STREET PHILADELPHIA, PA 19104-2891			EXAMINER WILLIAMS, LAWRENCE B	
			ART UNIT 2611	PAPER NUMBER
			MAIL DATE 12/14/2007	DELIVERY MODE PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

Office Action Summary	Application No. 10/798,762	Applicant(s) COSTANTINI, FRANK A.	
	Examiner Lawrence B. Williams	Art Unit 2611	

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

- 1) ☒ Responsive to communication(s) filed on 11 March 2004.
- 2a) ☐ This action is **FINAL**. 2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

- 4) ☒ Claim(s) 21-38 is/are pending in the application.
- 4a) Of the above claim(s) _____ is/are withdrawn from consideration.
- 5) ☐ Claim(s) _____ is/are allowed.
- 6) ☒ Claim(s) 21-38 is/are rejected.
- 7) ☐ Claim(s) _____ is/are objected to.
- 8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☒ The drawing(s) filed on 11 March 2004 is/are: a) ☒ accepted or b) ☐ objected to by the Examiner.
 Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
 Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All b) ☐ Some * c) ☐ None of:
1. ☐ Certified copies of the priority documents have been received.
2. ☐ Certified copies of the priority documents have been received in Application No. _____.
3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).
- * See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

- | | |
|---|---|
| 1) <input checked="" type="checkbox"/> Notice of References Cited (PTO-892) | 4) <input type="checkbox"/> Interview Summary (PTO-413)
Paper No(s)/Mail Date. _____ |
| 2) <input type="checkbox"/> Notice of Draftsperson's Patent Drawing Review (PTO-948) | 5) <input type="checkbox"/> Notice of Informal Patent Application |
| 3) <input checked="" type="checkbox"/> Information Disclosure Statement(s) (PTO/SB/08)
Paper No(s)/Mail Date _____ | 6) <input type="checkbox"/> Other: _____ |

DETAILED ACTION

Claim Rejections - 35 USC § 103

1. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

2. Claims 21-22, 26, 37 are rejected under 35 U.S.C. 103(a) as being unpatentable over Li (US Patent 6,549,587 B1) in view of Kennedy et al. (US Patent 5,903,603).

(1) With regard to claim 21, Li discloses in Fig. 24, a method for identifying a far-end modem type (col. 54, lines 44-46, 49-51), comprising: receiving a response signal (Remote ANS(am), AA, AC indications to call negotiator 502 shown as dotted line in Fig. 24) from a far-end modem in response to a transmitted V.8 ANS_{am} tone (LOCAL ANS(am), AA, AC indications from call negotiator 502); and determining from the response signal whether the far-end modem is a commercial modem (col. 54, line 49-col. 55, line 5; Li discloses determining a particular standard (V.22, V.32bis, V.34, V.90, etc., all known in the art as commercial modems) of the modems. Li does not however teach determining from the response signal whether the far-end modem is a secure modem.

However, Kennedy et al. teaches establishing a secure communication channel between two (STU) secure telephone units (col. 1, lines 22-29) wherein a remote modem responds to a 2100 Hz (It is known in the art that a 2100 Hz tone is used as a V.8 ANS_{am} tone) during establishment of the secure channel (col. 2, lines 44- 55). Since establishment of a secure

Art Unit: 2611

communication channel is the objective, it would be inherent that the response would signify a secure telephone/modem capability. Kennedy et al. also discloses the modems involved built according to the FSVS (Future Secure voice System) -210 (pg. 11, lines 34-37).

It would have been obvious to one skilled in the art at the time of invention to incorporate the teachings of Kennedy et al. as a method of establishing a secure communication channel.

(2) With regard to claim 22, Li also discloses the method of claim 21, wherein determining whether the far-end modem is a commercial modem or a secure modem comprises determining whether the far-end modem is a V.series modem (col. 5, lines 3-4)

Li does not determine whether the modem is a future secure voice system modem. However, Kennedy et al. discloses determining whether the far end modem is a future secure modem. Kennedy et al. discloses the modems involved built according to the FSVS (Future Secure voice System) -210 (pg. 11, lines 34-37).

It would have been obvious to one skilled in the art at the time of invention to incorporate the teachings of Kennedy et al. as a method of establishing a secure communication channel.

(3) With regard to claim 26, Kennedy et al. also discloses determining whether the response signal includes phase shifts; and if the response signal includes phase shifts, determining that the far-end modem is a secure modem. Kennedy et al. teaches establishing a secure communication channel between (STU) secure telephone units (col. 1, lines 22-28) wherein a remote modem transmits as a response signal, a P1800 (Pseudo 1800) Hz signal corresponding to +45 and -45 degree phase shifts (col. 2, lines 51-59). Kennedy et al. also discloses the modems involved built according to the FSVS (Future Secure Voice System) -210 (pg. 11, lines 34-37). Thus the responding STU would be recognized as a secure modem.

Art Unit: 2611

It would have been obvious to one skilled in the art at the time of invention to incorporate the teachings of Kennedy et al. as a training procedure between two secure communication systems (col. 1, lines 5-12).

(4) With regard to claim 37, claim 37 discloses the method of claim 21 implemented via computer readable medium with computer executable instructions. Li also discloses his invention can be implemented by a software embodiment which would inherently include a computer readable medium with computer executable instructions.

3. Claim 23 is rejected under 35 U.S.C. 103(a) as being unpatentable over Li (US Patent 6,549,587 B1) in view of Kennedy et al. (US Patent 5,903,603) as applied to claim 22 above, and further in view of Chen et al. (US Patent 6,560,321 B1).

Claim 23 inherits all limitations of claim 22 above. As noted above, the combination of Li and Kennedy et al. disclose all limitations of claim 22 above. They do not disclose determining whether the response signal is a V.CM tone; if the response signal is a V.8 CM tone, determining that the far-end modem is a V.8 modem.

However, Chen et al. teaches determining whether a response signal is a V.CM tone; if the response signal is a V.8 CM tone (Chen et al. teaches the Rn/Rp distinguishable from a conventional V.8 CM signal), determining that the far-end modem is a V.8 modem (Chen et al. teaches the V.8 CM signal typically transmitted in response to an ANS_{am} signal is known as part of a conventional V.8 procedure (col. 9, lines 21-25; lines 44-52) inherently implying a V.8 modem).

Art Unit: 2611

One skilled in the art could have easily incorporated the teachings of Chen et al. into the invention of Li as a method of determining a responding modem's capabilities.

4. Claims 24-25 are rejected under 35 U.S.C. 103(a) as being unpatentable over Li (US Patent 6,549,587 B1) in view of Kennedy et al. (US Patent 5,903,603) as applied to claim 21 above, and further in view of Scott (US Patent 5,349,635).

(1) With regard to claim 24. Claim 24 inherits all limitations of claim 21 above. As noted above, the combination of Li and Kennedy et al. disclose all limitations of claim 21. Furthermore Kennedy et al. also teaches determining whether the response signal has a nominal frequency of about 1800 Hz, and if the response signal has a nominal frequency of about 1800 Hz, determining from the response signal whether the far-end modem is or a secure modem (col. 2, lines 55-59). Since establishment of a secure communication channel is the objective, it would be inherent that the response would signify a secure telephone/modem capability. Kennedy et al. also discloses the modems involved built according to the FSVS (Future Secure Voice System) - 210 (pg. 11, lines 34-37).

The teachings of Li and Kennedy et al. do not however teach determining from the response signal if the far-end modem is a V.32 modem.

However, Scott teaches in Fig. 5, detecting an 1800 Hz V.32 signal AA (515) in response to a transmitted signal and then switching to a V.32 mode of operation (520, 525; col. 3, lines 60-64) inherently signifying a V.32 modem.

One skilled in the art could have easily incorporated the teachings of Scott and would have been motivated to do to detect modem capabilities of a responding modem.

Art Unit: 2611

(2) With regard to claim 25, Scott also discloses determining whether the response signal includes phase shifts (col. 3, lines 49-51); and if the response signal does not include phase shifts, determining that the far-end modem is a V.32 modem (col. 3, lines 60-64). Scott discloses detecting a V.32 answering tone at 2100 Hz with phase reversals (phase shifts) conforming to CCITT V.32 standards. Scott also discloses detecting an 1800 Hz signal which is a part of the V.32 call establishment. Since Scott discloses both the 2100 Hz with phase reversals and the 1800 Hz signal (no phase reversals) conforming to V.32 standards, it is inherent that the 1800 Hz, without phase reversals signifies a V.32 modem capability.

It would have been obvious to one skilled in the art at the time of invention to incorporate the teachings of Scott (V.32 standards) as a method of identifying a modem type.

5. Claims 27-28 are rejected under 35 U.S.C. 103(a) as being unpatentable over Li (US Patent 6,549,587 B1) in view of Kennedy et al. (US Patent 5,903,603) as applied to claim 21 above, and further in view of Dimolitsas et al. (US Patent 5,963,621).

(1) With regard to claim 27, claim 27 inherits all limitations of claim 21, above. As noted above, the combination of Li and Kennedy et al. disclose all limitations of claim 21. They do not however disclose determining from the response signal, an operational mode of the far-end modem.

However, Dimolitsas et al. discloses a secure communication system wherein he teaches a responder modem (secure terminal) responding with a P1800 Hz signal with no phase reversals used to indicate an interoperable mode and a P1800 Hz with phase reversals to indicate an alternate mode of operation for the secure responder terminal (col. 20, lines 20-31).

Art Unit: 2611

It would have been obvious to one skilled in the art at the time of invention to incorporate the teachings of Dimolitsas et al. as a method of signifying operational modes of the modems as used by Dimolitsas et al.

(2) With regard to claim 28, Dimolitsas et al. also discloses determining whether the response signal includes phase reversals; and if the response signal includes phase reversals, determining that the far-end modem is a future secure voice system modem in alternate mode (col. 20, lines 20-31; col. 5, lines 18-29).

It would have been obvious to one skilled in the art at the time of invention to incorporate the teachings of Dimolitsas et al. as a method of distinguishing operational modes of the modems as used by Dimolitsas et al.

6. Claims 29, 30 are rejected under 35 U.S.C. 103(a) as being unpatentable over Li (US Patent 6,549,587 B1) in view of Kennedy et al. (US Patent 5,903,603) and Dimolitsas et al. (US Patent 5,963,621) as applied to claim 27 above, and further in view of Mihm, Jr. (US Patent 5,003,593).

(1) With regard to claim 29, claim 29 inherits all limitations of claim 27 above. As noted above, the combination of Li, Kennedy et al. and Dimolitsas et al. disclose all limitations of claim 27. They do not however disclose wherein determining the operational mode of the far-end modem comprises: determining whether the response signal includes a 128 dibit gap; and if the response signal includes a 128 dibit gap, determining that the far-end modem is a future secure voice system modem in half-duplex mode.

Art Unit: 2611

However, Mihm, Jr. discloses a teleconferencing method for a secure key management system wherein he teaches a half-duplex communications mode (col. 2, lines 33-34) between secure terminals (col. 2, lines 18-20). Mihm, Jr. also teaches a terminal transmitting an access domain message in half-duplex to conferenced terminals by transmitting P1800 data, stopping transmitting for 256 bits and then continuing transmitting P1800 data (col. 3, lines 1-13). The stopping for 256 bits is equivalent to applicant's claimed 128 dibit gap, since a dibit is defined as any one of four patterns from two consecutive bits which in this case Mihm, Jr.'s stopping transmitting for 256 bits is equivalent to applicant's 128 dibit gap.

It would have been obvious to one skilled in the art at the time of invention to incorporate the teachings of Mihm, Jr. as a method of simply identifying a half-duplex mode of operation between secure terminals as Mihm, Jr. has taught.

(2) With regard to claim 30, Dimolitsas et al. discloses that a P1800 Hz tone without phase reversals from a responder is used to indicate an interoperable mode of operation (col. 20, lines 21-25), which would inherently imply the ability to determine whether the response signal includes phase reversals and also discloses the P1800 Hz tone being transmitted without a gap in signal energy (col. 16, lines 2-4), also inherently implying that a gap could be detected. Thus the invention of Dimolitsas et al. has the ability to determine whether the response signal includes phase reversals and a 128 dibit gap and determine that the far-end modem is a future secure modem (col. 5, lines 18-29).

Art Unit: 2611

It would have been obvious to one skilled in the art at the time of invention to incorporate the teachings of Dimolitsas et al. as a method of initiating a secure communication system in an operable mode of operation as used by Dimolitsas et al.

6. Claims 31-35, 38 are rejected under 35 U.S.C. 103(a) as being unpatentable over Dimolitsas et al. (US Patent 5,963,621) in view of Brent et al. (US Patent 6,788,651 B1).

(1) With regard to claim 31, Dimolitsas et al. discloses a method for determining a far-end modem type, comprising: receiving a response signal (col. 20, lines 33-37) from a far-end modem in response to a transmitted P1800 Hz tone (col. 20, lines 27-31) with phase reversals; and determining from the response signal whether the far-end modem is a secure modem. It would be obvious that the response signifies the responder capable of secure communications (secure modem) since Dimolitsas et al. discloses this procedure as part of the Secure Terminals Protocols (col. 20, Secure Terminal Protocols, lines 9-52). Dimolitsas et al. does not disclose determining from the response signal whether the far-end modem is a commercial modem.

However, Brent et al. discloses a pair of 600 Hz and 3000Hz tones being transmitted in response to a 1800 Hz tone being used to indicate that a V.32 (commercial modem) modem connection is starting to take place between two corresponding terminals (col. 6, lines 45-63, specifically, lines 51-56). It is inherent that the 600 and 3000 Hz response tones signify a V.32 (commercial modem).

It would have been obvious to one skilled in the art at the time of invention to incorporate the teachings of Brent et al. as a method of providing automode detection between terminals.

Art Unit: 2611

(2) With regard to claim 32, claim 32 inherits all limitations of claim 31 above. As noted in the rejection of claim 31, Dimolitsas et al. discloses determining from the response signal whether the far-end modem is a secure modem. Brent et al. also discloses determining that the far-end modem is a V.32 modem (col. 6, lines 51-56).

It would have been obvious to one skilled in the art at the time of invention to incorporate the teachings of Brent et al. as a method of providing automode detection between terminals.

(3) With regard to claim 33, claim 33 inherits all limitations of claim 32, above. Furthermore Brent et al. also discloses determining whether the determining if the response signal includes a V.32 AC; and if the response signal includes a V.32 AC (V.32 AC is a pair of 600Hz and 3000 Hz tones, which are disclosed by Brent et al.), determining that the far-end modem is a V.32 mode (col. 6, lines 51-56).

It would have been obvious to one skilled in the art at the time of invention to incorporate the teachings of Brent et al. as a method of providing automode detection between terminals.

(4) With regard to claim 34, Dimolitsas et al. also discloses the method of claim 31, further comprising: determining whether the response signal includes a future secure voice system ("FSVS") Message A (col. 20, line 61-col. 21 line 14); and if the response signal includes an FSVS Message A, determining that the far-end modem is an FSVS modem in alternate signaling mode (col. 22, lines 17-27). Dimolitsas et al. discloses detection of the message A (pertinent to an FSVS system) signal inherently implying applicant's first determination step and Dimolitsas et al. discloses a call setup in the alternate mode as a result of MSG A or MSG B.

(5) With regard to claim 35, claim 35 inherits all limitations of claim 31 above. As noted above, Brent et al. discloses whether the response signal includes a V.32 AC (pair of 600 Hz and

Art Unit: 2611

3000 Hz constitute a V.32 AC, col. 6, lines 51-56) and Dimolitsas et al. teaches determining whether the response signal includes a future secure voice system ("FSVS") Message A.

Furthermore, Dimolitsas et al. also discloses determining that a far-end modem is an FSVS modem in interoperable mode with a response signal including neither a V.32 AC nor an FSVS Message A (col. 20, lines 21-25; col. 24, line 64-67).

(5) With regard to claim 38, claim 38 discloses the method of claim 31 implemented via computer readable medium with computer executable instructions. Dimolitsas et al. does not explicitly teach a computer readable medium with computer readable instructions for performing the method. However, Dimolitsas et al. discloses the SIU (secure interface unit, Fig. 3, element 10, which performs the method) as a component of the DSP, 30. It would be obvious to one skilled in the art that the SIU method would be performed by executable instructions in the SIU.

7. Claim 36 is rejected under 35 U.S.C. 103(a) as being unpatentable over Dimolitsas et al. (US Patent 5,963,621) in view of Brent et al. (US Patent 6,788,651 B1) as applied to claim 31 above, and further in view of Goldstein (US Patent 5,317,594).

Claim 36 inherits all limitations of claim 31 above. As noted above, the combination of Dimolitsas et al. and Brent et al. disclose all limitations of claim 31. Dimolitsas et al. also discloses an alternate and interoperable mode of operation between secure terminals associated with a 2100 Hz tone (col. 27, lines 36-40). They do not disclose monitoring an incoming channel for energy at 2100 Hz; and if 2100 Hz energy is present in the incoming channel for at least about one second, then determining whether the far-end modem v.32 compliant commercial modem.

Art Unit: 2611

However, Goldstein teaches a method for identifying a modem in Fig. 4, wherein he teaches CCITT Recommendations for V.32 handshake, where he teaches the modem sending a an ANS tone of 2100 Hz for one or more seconds, and upon receipt a second modem replying (it would be inherent that the second modem would be monitoring the channel for at least one second to detect and response to the 2100 Hz energy). Since Goldstein teaches this procedure as CCITT Recommendations for V.32 handshake, it would be obvious that the second modem's response would signify a V.32 compliant modem.

It would have been obvious to one skilled in the art at the time of invention to incorporate the teachings of Goldstein as a method of identifying V.fast type modems (col. 1, lines 60-66).

Double Patenting

7. The nonstatutory double patenting rejection is based on a judicially created doctrine grounded in public policy (a policy reflected in the statute) so as to prevent the unjustified or improper timewise extension of the "right to exclude" granted by a patent and to prevent possible harassment by multiple assignees. A nonstatutory obviousness-type double patenting rejection is appropriate where the conflicting claims are not identical, but at least one examined application claim is not patentably distinct from the reference claim(s) because the examined application claim is either anticipated by, or would have been obvious over, the reference claim(s). See, e.g., *In re Berg*, 140 F.3d 1428, 46 USPQ2d 1226 (Fed. Cir. 1998); *In re Goodman*, 11 F.3d 1046, 29 USPQ2d 2010 (Fed. Cir. 1993); *In re Longi*, 759 F.2d 887, 225 USPQ 645 (Fed. Cir. 1985); *In re Van Ornum*, 686 F.2d 937, 214 USPQ 761 (CCPA 1982); *In re Vogel*, 422 F.2d 438, 164 USPQ 619 (CCPA 1970); and *In re Thorington*, 418 F.2d 528, 163 USPQ 644 (CCPA 1969).

A timely filed terminal disclaimer in compliance with 37 CFR 1.321(c) or 1.321(d) may be used to overcome an actual or provisional rejection based on a nonstatutory double patenting ground provided the conflicting application or patent either is shown to be commonly owned with this application, or claims an invention made as a result of activities undertaken within the scope of a joint research agreement.

Effective January 1, 1994, a registered attorney or agent of record may sign a terminal disclaimer. A terminal disclaimer signed by the assignee must fully comply with 37 CFR 3.73(b).

Art Unit: 2611

8. Claims 1-10 of U.S. Patent 6,768,771 B1 contain every element of claims 21-30 of the instant application and as such anticipate(s) claims 21-30 of the instant application.

Regarding claim 21, claim 1 of US Patent 6,768,771 B1 discloses a method for identifying a far-end modem type, comprising: receiving a response signal from a far-end modem in response to a transmitted V.8 ANS_{am} tone (lines 6-7); and determining from the response signal whether the far-end modem is a commercial modem or a secure modem (lines 8-9).

Regarding claims 22-30, claims 2-10, respectively of US Patent 6,768,771 B1 disclose the exact limitations of claims 22-30 of the instant application.

9. Claims 11-16 of U.S. Patent 6,768,771 B1 contain every element of claims 31-36 of the instant application and as such anticipates claims 31-36 of the instant application.

Regarding claim 31, claim 11 of US Patent 6,768,771 B1 discloses a method for determining a far-end modem type, comprising: receiving a response signal from a far-end modem in response to a transmitted P1800 Hz tone with phase reversals (lines 4-8); and determining from the response signal whether the far-end modem is a commercial modem or a secure modem (lines 9-10).

Regarding claims 32-36, claims 12-16, respectively of US Patent 6,768,771 B1 disclose the exact limitations of claims 32-36 of the instant application.

10. Claim 19 of U.S. Patent 6,768,771 B1 contains every element of claim 37 of the instant application and as such anticipates claim 37 of the instant application.

Art Unit: 2611

Claim 19 of US Patent 6,768,771 B1 discloses a computer-readable medium having stored thereon computer executable instructions for performing a method for identifying a far-end modem type, the method comprising: receiving a response signal from a far-end modem in response to a transmitted V.8 ANS_{am} tone (lines 5-6); and determining from the response signal whether the far-end modem is a commercial modem or a secure modem (lines 7-8).

11. Claim 20 of U.S. Patent 6,768,771 B1 contains every element of claim 38 of the instant application and as such anticipates claim 38 of the instant application.

Claim 20 of US Patent 6,768,771 B1 discloses a computer-readable medium having stored thereon computer executable instructions for performing a method for identifying a far-end modem type, the method comprising: receiving a response signal from a far-end modem in response to a transmitted P1800 Hz tone with phase reversals (lines 6-9); and determining from the response signal whether the far-end modem is a commercial modem or a secure modem (10-11).

Conclusion

12. The prior art made of record and not relied upon is considered pertinent to applicant's disclosure.

a.) Yoshida et al. discloses in US Patent 6,075,620 Communication Apparatus Having Communication Function Complying with ITU-T V.8 and V.34 Recommendations.

b.) Fruth discloses in US Patent 7,126,711 B2 Voice/Facsimile/Modem Call Discrimination Method For Voice Over Packet Networks.

Art Unit: 2611

c.) Maeda discloses in US Patent 5,847,842 Facsimile Apparatus Having Protocol For Identifying Modem Type.

d.) Abdelilah et al. discloses in US 6,757,325 B1 Methods, Modems and Computer Program Products For Identification of a Modem Type and Adjustment of a Communication Configuration Based on Modem Type.

e.) Verreault discloses in US Patent 6,434,169 B1 VoiceBand/Modem Signal Relay.

f.) Legare discloses in US Patent 6,400,802 B1 Method and Apparatus For Performing Transmission Line Testing.

g.) Brown et al. discloses in US Patent 5,732,104 Signalling Techniques and Device For High Speed Data Transmission Over VoiceBand Channels.

h.) Goldstein discloses in US 5,317,594 Systems For And Method Of Identifying V.Fast Modem Within Existing Automatic Interworking Procedure Standards.

i.) Livishin discloses in US Patent 6,501,790 B1 Method and Apparatus For Providing High Speed Modem Replay Using Locally Connecting Modems.

13. Any inquiry concerning this communication or earlier communications from the examiner should be directed to Lawrence B Williams whose telephone number is 571-272-3037. The examiner can normally be reached on Monday-Friday (8:00-6:00).

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Ghayour Mohammad can be reached on 571-272-3021. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.


Art Unit: 2611

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

Lawrence B. Williams

lbw

December 10, 2007


DAVID C. PAYNE
SUPERVISORY PATENT EXAMINER